

WWT High-Temperature Nonrotating Protector - NRP



Model HT Specifications

NRP Model	HT-350	HT-500	HT-550
Drill Pipe Size	3-1/2"	5"	5-1/2"
Sleeve OD	5-1/2"	7-1/4"	7-3/4"
Collar OD	5"	6-1/2"	7"
Sleeve Length	10"	9-1/2"	10"
Overall Length	20"	19-1/2"	20"
Side-Load Rating	1,500 lbs.	2,000 lbs.	2,000 lbs.
Total Flow Area			
5-1/2" Casing	N/R	N/R	N/R
7" Casing	8.3 in. ²	N/R	N/R
9-5/8" Casing	37 in. ²	18 in. ²	16.3 in. ²
13-3/8" Casing	99 in. ²	78 in. ²	77 in. ²
Collar Material	6061-T651 Extruded Aluminum Alloy		
Sleeve Material	HNBR		
Max. Temperature	300° F (149° C)		

N/R = Not Recommended

Features and Benefits

- Positive protection against casing and riser wear during drilling operations.
- Significant torque reduction created by our patented fluid bearing design allows for improved ROP.
- Compatible with most oil-, synthetic- and water-based drilling fluids.
- Optimum operating performance range of 30 - 250 RPM.
- Reduces drillstring and surface equipment stress.



- Each assembly accepts up to 30,000 lbs. of axial force before slippage.
- Installation time: less than 1 minute.
- Free, no-obligation confidential torque, drag and wear analysis may be obtained via our website.
- More than 15 years of global leadership in controlling wellbore and riser torque, drag and wear in some of the world's most challenging drilling environments.



HOUSTON, TEXAS
Toll-free: 800-998-0802
Tel: 281-345-8019
Fax: 281-345-8177

ANAHEIM, CALIFORNIA
Toll-free: 800-465-0127
Tel: 714-632-0810
Fax: 714-632-1334

ABERDEEN, SCOTLAND
Tel: 44-1224-224646
Fax: 44-1224-224647

www.wwtco.com

Western Well Tool

Innovative Products for Drilling, Completion and Intervention Profitability

To find out more about Western Well Tool Nonrotating Protectors or our Coiled Tubing Tractors, visit our website.