

WWT Super Slider Nonrotating Protector - NRP



Model SS Specifications

NRP Model	SS-350	SS-400	SS-450	SS-500	SS-550	SS-578	SS-658
Drill Pipe Size	3-1/2"	4"	4-1/2"	5"	5-1/2"	5-7/8"	6-5/8"
Sleeve OD	5-1/2"	5-7/8"	6-3/4"	7-1/4"	7-3/4"	8"	9"
Collar OD	5"	5-1/2"	6"	6-1/2"	7"	7-3/8"	8-1/8"
Sleeve Length	10"	10"	10"	9-1/2"	10"	10"	12"
Overall Length	20"	20"	20"	19-1/2"	20"	20"	22"
Side-Load Rating	2,200 lbs.	2,200 lbs.	3,000 lbs.	3,000 lbs.	3,000 lbs.	3,500 lbs.	3,500 lbs.
Total Flow Area							
5-1/2" Casing	N/R	N/R	N/R	N/R	N/R	N/R	N/R
7" Casing	7.8 in. ²	N/R	N/R	N/R	N/R	N/R	N/R
9-5/8" Casing	36.5 in. ²	35 in. ²	26 in. ²	20 in. ²	15.3 in. ²	12.7 in. ²	N/R
13-3/8" Casing	98.5 in. ²	97 in. ²	88 in. ²	82 in. ²	76 in. ²	74 in. ²	62.5 in. ²
Collar Material	6061-T651 Extruded Aluminum Alloy						
Sleeve Material	High-Temperature Polyurethane and Advanced Low-Friction Polymer Pads						
Max. Temperature	230° F (110° C)						

N/R = Not Recommended

Features and Benefits

- Heavy-duty construction to accept greater contact forces.
- Positive protection against casing and riser wear during drilling operations.
- Significant torque reduction created by our patented fluid bearing design allows for improved ROP.
- Low-friction external pads provide measurable drag reduction in high-angle wells.
- Compatible with most oil-, synthetic- and water-based drilling fluids.



- Optimum operating performance range of 20 - 250 RPM.
- Reduces drillstring and surface equipment stress.
- Each assembly accepts up to 30,000 lbs. of axial force before slippage.
- Installation time: less than 1 minute.
- Free, no-obligation, confidential torque, drag and wear analysis may be obtained via our website.
- More than 15 years of global leadership in controlling wellbore and riser torque, drag and wear in some of the world's most challenging drilling environments.



HOUSTON, TEXAS
Toll-free: 800-998-0802
Tel: 281-345-8019
Fax: 281-345-8177

ANAHEIM, CALIFORNIA
Toll-free: 800-465-0127
Tel: 714-632-0810
Fax: 714-632-1334

ABERDEEN, SCOTLAND
Tel: 44-1224-224646
Fax: 44-1224-224647

Western Well Tool

www.wwtco.com

Innovative Products for Drilling, Completion and Intervention Profitability

To find out more about Western Well Tool Nonrotating Protectors or our Coiled Tubing Tractors, visit our website.