

# Slider-Clamp Cable Protector

Reduce drag running tubing • Protect cable and tubing from damage

Fast and easy installation and removal • Can be reused to save time and money on re-runs



Slider-Clamp Model*	Tubing Size	Cable Size	OD	Overall Length	Max Temp	Material	Banding
B-278-128R-LF	2-7/8"	1.28" Round	5.5"	5.5"	230°F	Low-Friction Polymer with Rubber ID	One 1-1/4" Band
B-278-163F-LF	2-7/8"	Up to 1.63" Wide Flat	4.4"	5.5"	230°F	Low-Friction Polymer with Rubber ID	One 1-1/4" Band

\*Other sizes available upon request.

## Features and Benefits:

- Low friction proprietary polymer reduces sliding friction by up to 50%, while inside grips the pipe and cable.
- Durable downhole-proven materials protect cable and tubing.
- Help run electrical submersible pumps (ESPs) to high angles in horizontal and ERD wells.
- Reusable design to save time and money on re-runs.
- 1/4" & 3/8" capillary tubing slots for securing injection tubing or chem lines.



© 2026 WWT North America Holdings, Inc. All rights reserved.  
WWT International is a registered trademark of WWT North America Holdings, Inc.

WWT International supports your operations from start to finish with full-service onsite mobilization and support 24/7.

To find out more, visit: [www.wwtco.com](http://www.wwtco.com)



PS011B